












超音波感測器

功能 / 規格一覽表

檢測方式	反射型					對照型	
型號	E4C-DS30 + E4C-UDA□□	E4C-DS80 + E4C-UDA□□	E4C-DS30L + E4C-UDA□□	E4C-DS80L + E4C-UDA□□	E4C-DS100 + E4C-UDA□□	E4E2-TS50C1	
外觀							
特色	<ul style="list-style-type: none"> 螺絲型正面發音 數位顯示 教導功能 具類比輸出功能 		<ul style="list-style-type: none"> 螺絲型側面發音 數位顯示 教導功能 具類比輸出功能 		<ul style="list-style-type: none"> 螺絲型正面發音 數位顯示 教導功能 具類比輸出功能 	<ul style="list-style-type: none"> 內建放大器 附穩定指示燈 	
檢測距離	1,000		85~735mm		85~735mm	110~910mm	
	500						500mm
	400						
	300	60~275mm		60~275mm			
	200						
100							
電源電壓	DC12~24V					DC24V	
輸出方式	NPN輸出	●	●	●	●	●	●
	PNP輸出	●	●	●	●	●	—
保護等級	IP65 (感應器部分) IP50 (放大器部分)					IP64	
規格	CE	●	●	●	●	●	●